

## PRINTED U.S. FORMAT

MANUFACTURED BY : ABC MANUFACTURING		DATE OF MFG. : 12/2011	
GVWR : 3175 KG (7000 LB)			
GAWR (EACH AXLE)	WITH TIRES	RIMS AT	COLD
1588 KG (3500 LB)	ST205-75R15	5J X 15	345 KPA (50PSI) SINGLE
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE			
V.I.N. : <b>XXXA1V42581407002</b>		TYPE : TRAILER	VACUMM-40

  

	<b>TIRE AND LOADING INFORMATION</b>	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION	FOR REORDER CALL PMCS (818) 957-5649 PART # LS-CL-D2	XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002
	The weight of cargo should never exceed 2,325 kg or 5,125 lbs.			
TIRE	SIZE	COLD TIRE PRESS.		
FRONT	ST205-75R15	345 KPA (50 PSI)		
INTER	NONE			
REAR	ST205-75R15	345 KPA (50 PSI)		
SPARE	NONE			

XXXA1V42581407002



## PRINTED BILINGUAL FORMAT

MANUFACTURED BY / FABRIQUÉ PAR : ABC MANUFACTURING		DATE : 12/2011	
GVWR / PNBV : 3175 KG (7000 LB)			
GAWR (EACH AXLE) /			COLD INFL. PRESS. / PRESS.
PNBE (CHAQUE ESSIEU)	TIRE / PNEU	RIM / JANTE	DE GONFL. À FROID
1588 KG (3500 LB)	ST205-75R15	5J X 15	KPA (PSI / LPC)
THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. / CE VÉHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA SÉCURITÉ DES VÉHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION			
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE			
V.I.N./N.I.V. : <b>XXXA1V42581407002</b>		TYPE : TRA/REM	VACUMM-40

  

	<b>TIRE AND LOADING INFORMATION</b> <b>RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT</b>	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS	FOR REORDER CALL PMCS (818) 957-5649 PART # LS-CL-D2	XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002
	The weight of cargo should never exceed Le poids du chargement ne doit jamais dépasser 2,325 kg or 5,125 lbs.			
TIRE / PNEU	SIZE / DIMENSIONS	COLD TIRE PRESS. / PRESS. DES PNEUS À FROID		
FR/AV	ST205-75R15	345 KPA (50 PSI)		
INT/INT	NONE/AUCUN			
RR/AR	ST205-75R15	345 KPA (50 PSI)		
SPARE/DE SECOURS	NONE/AUCUN			

XXXA1V42581407002



## PRINTED CANADA MANUFACTURER

MANUFACTURED BY / FABRIQUÉ PAR: ABC MANUFACTURING		86761 ALLEN RD. 93			
		LUCKNOW, ONTARIO N0G 2H0			
TYPE : TRA / REM		VACUMM-40		DATE: 12/2011	
GVWR / PNBV: 3175 KG (7000 LB)		V.I.N. / N.I.V. <b>XXXA1V42581407002</b>			
GAWR (EACH AXLE) /				COLD INFL. PRESS. /	
PNBE (CHAQUE ESSIEU)	TIRE / PNEU	RIM / JANTE		PRESS. DE GONFL. À FROID	
1588 KG (3500 LB)	ST205-75R15	5J X 15		KPA (PSI / LPC)	
CE VÉHICULE EST CONFORME À TOUTES LES NORMES FEDERALES DE SURERE AUTOMOBILE EN VIGUEUR AU CANADA À LA DATE FABRICATION INDIQUEE CI-DESSUS.					
V.I.N./N.I.V. : <b>XXXA1V42581407002</b>		VACUMM-40			

  

	<b>TIRE AND LOADING INFORMATION</b> <b>RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT</b>	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS	FOR REORDER CALL PMCS (818) 957-5649 PART # LS-CL-D2	XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002 XXXXA1V42581407002
	The weight of cargo should never exceed Le poids du chargement ne doit jamais dépasser 2,325 kg or 5,125 lbs.			
TIRE / PNEU	SIZE / DIMENSIONS	COLD TIRE PRESS. / PRESS. DES PNEUS À FROID		
FR/AV	ST205-75R15	345 KPA (50 PSI)		
INT/INT	NONE/AUCUN			
RR/AR	ST205-75R15	345 KPA (50 PSI)		
SPARE/DE SECOURS	NONE/AUCUN			

XXXA1V42581407002

