



BLANK FORMAT

 <div style="background-color: black; color: yellow; padding: 2px; text-align: center; font-weight: bold;"> TIRE AND LOADING INFORMATION RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT </div> <div style="border: 1px solid red; height: 60px; margin-top: 10px;"></div> <div style="background-color: black; color: yellow; padding: 2px; text-align: center; font-weight: bold; margin-top: 5px;"> SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS </div>	<table border="1" style="width: 100%; border-collapse: collapse; height: 100px;"> <tr><td style="width: 20%;"></td><td style="width: 20%;"></td><td style="width: 20%;"></td><td style="width: 20%;"></td><td style="width: 20%;"></td></tr> </table>					

TM and Copyright 2016 PMCS, Inc.


PRINTED U.S. FORMAT

MANUFACTURED BY : ABC MANUFACTURING		DATE OF MFG. : 05/2014																								
GVWR : 3175 KG (7000 LB)																										
GAWR (EACH AXLE)	WITH TIRES	RIMS AT	COLD																							
1588 KG (3500 LB)	ST205-75R15 6 PLY	15 X 5 J	345 KPA (50 PSI) SINGLE																							
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE																										
V.I.N. : XXXA1U827DM407001		TYPE : TRAILER																								
		UTILITY - 8'																								
 <div style="background-color: black; color: yellow; padding: 2px; text-align: center; font-weight: bold;"> TIRE AND LOADING INFORMATION RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT </div> <p style="text-align: center;">The weight of cargo should never exceed 2,769 kg or 6,105 lbs.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>TIRE</th> <th>SIZE</th> <th>COLD TIRE PRESS.</th> </tr> </thead> <tbody> <tr> <td>FRONT</td> <td>ST205-75R15 6 PLY</td> <td>345 KPA (50 PSI)</td> </tr> <tr> <td>INTER</td> <td>NONE</td> <td></td> </tr> <tr> <td>REAR</td> <td>ST205-75R15 6 PLY</td> <td>345 KPA (50 PSI)</td> </tr> <tr> <td>SPARE</td> <td>NONE</td> <td></td> </tr> </tbody> </table> <div style="background-color: black; color: yellow; padding: 2px; text-align: center; font-weight: bold; margin-top: 5px;"> SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS </div>	TIRE	SIZE	COLD TIRE PRESS.	FRONT	ST205-75R15 6 PLY	345 KPA (50 PSI)	INTER	NONE		REAR	ST205-75R15 6 PLY	345 KPA (50 PSI)	SPARE	NONE		<div style="text-align: center; font-weight: bold; margin-bottom: 10px;"> XXXXA1U827DM407001 </div> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> </tr> <tr> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> </tr> </table> <div style="text-align: center; margin-top: 10px;"> FOR REORDER CALL PMCS (818) 957-5649 PART # LS-CL-D4 </div>						XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001
TIRE	SIZE	COLD TIRE PRESS.																								
FRONT	ST205-75R15 6 PLY	345 KPA (50 PSI)																								
INTER	NONE																									
REAR	ST205-75R15 6 PLY	345 KPA (50 PSI)																								
SPARE	NONE																									
XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001																						



XXXA1U827DM407001

PRINTED BILINGUAL FORMAT

MANUFACTURED BY / FABRIQUÉ PAR : ABC MANUFACTURING		DATE : 05/2014																								
GVWR / PNBV : 3175 KG (7000 LB)																										
GAWR (EACH AXLE) / PNBE (CHAQUE ESSIEU)	TIRE / PNEU	RIM / JANTE	COLD INFL. PRESS. / PRESS. DE GONFL. À FROID KPA (PSI / LPC)																							
1588 KG (3500 LB)	ST205-75R15 6 PLY	15 X 5 J	345 KPA (50 PSI) SINGLE																							
THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE. / CE VÉHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA SÉCURITÉ DES VÉHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION																										
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE																										
V.I.N./N.I.V. : XXXA1U827DM407001		TYPE : TRA/REM																								
		UTILITY - 8'																								
 <div style="background-color: black; color: yellow; padding: 2px; text-align: center; font-weight: bold;"> TIRE AND LOADING INFORMATION RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT </div> <p style="text-align: center;">The weight of cargo should never exceed Le poids du chargement ne doit jamais dépasser</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>TIRE / PNEU</th> <th>SIZE / DIMENSIONS</th> <th>COLD TIRE PRESS. / PRESS. DES PNEUS À FROID</th> </tr> </thead> <tbody> <tr> <td>FR/AV</td> <td>ST205-75R15 6 PLY</td> <td>345 KPA (50 PSI)</td> </tr> <tr> <td>INT/INT</td> <td>NONE/AUCUN</td> <td></td> </tr> <tr> <td>RR/AR</td> <td>ST205-75R15 6 PLY</td> <td>345 KPA (50 PSI)</td> </tr> <tr> <td>SPARE/DE SECOURS</td> <td>NONE/AUCUN</td> <td></td> </tr> </tbody> </table> <div style="background-color: black; color: yellow; padding: 2px; text-align: center; font-weight: bold; margin-top: 5px;"> SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS </div>	TIRE / PNEU	SIZE / DIMENSIONS	COLD TIRE PRESS. / PRESS. DES PNEUS À FROID	FR/AV	ST205-75R15 6 PLY	345 KPA (50 PSI)	INT/INT	NONE/AUCUN		RR/AR	ST205-75R15 6 PLY	345 KPA (50 PSI)	SPARE/DE SECOURS	NONE/AUCUN		<div style="text-align: center; font-weight: bold; margin-bottom: 10px;"> XXXXA1U827DM407001 </div> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> <td style="width: 20%;"></td> </tr> <tr> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> <td style="text-align: center;"> XXXXA1U827DM407001 </td> </tr> </table> <div style="text-align: center; margin-top: 10px;"> FOR REORDER CALL PMCS (818) 957-5649 PART # LS-CL-D4 </div>						XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001
TIRE / PNEU	SIZE / DIMENSIONS	COLD TIRE PRESS. / PRESS. DES PNEUS À FROID																								
FR/AV	ST205-75R15 6 PLY	345 KPA (50 PSI)																								
INT/INT	NONE/AUCUN																									
RR/AR	ST205-75R15 6 PLY	345 KPA (50 PSI)																								
SPARE/DE SECOURS	NONE/AUCUN																									
XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001	XXXXA1U827DM407001																						



XXXA1U827DM407001