

Thermal Vin & Tire Label with 3 VIN Strips

Labels are made of pressure-sensitive, white (glossy finish) imprintable material, UL approved for outdoor use.  
Labels are tamperproof, self-destructing “Void” pattern adhesive.  
Vin Label measures 6” x 1 7/8 ”, Tire Label measures 4 1/4” x 1 7/8”, on liner, perforated between each set.

BLANK LABELS COME ON A ROLL OF 500 SETS

1.875"



TIRE AND LOADING INFORMATION  
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

SEE OWNER'S  
MANUAL FOR  
ADDITIONAL  
INFORMATION  
VOIR LE MANUEL  
DE L'USAGER  
POUR PLUS DE  
RENSEIGNEMENTS

PRINTED DATA THRU OUR PROGRAM (VIN-EZE)  
U.S. FORMAT

1.875"

MANUFACTURED BY : ABC MANUFACTURING  
GVWR : 1356 KG (2990 LB)  
GAWR (EACH AXLE) WITH TIRES RIMS AT COLD  
1356 KG (2990 LB) ST205/75R15(C) 15 X 6 J 345 KPA (50 PSI) SINGLE  
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS  
IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE  
V.I.N.: XXXA1UB15C1054001 TYPE : TRAILER UTILITY 32' - TA

DATE OF MFG. : 12/2011



TIRE AND LOADING INFORMATION  
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should never exceed  
810 kg or 1,786 lbs.

| TIRE  | SIZE           | COLD TIRE PRESS. |
|-------|----------------|------------------|
| REAR  | ST205/75R15(C) | 345 KPA (50 PSI) |
| INTER | NONE           |                  |
| FRONT | NONE           |                  |
| SPARE | ST205/75R15(C) | 345 KPA( 50 PSI) |

SEE OWNER'S  
MANUAL FOR  
ADDITIONAL  
INFORMATION  
VOIR LE MANUEL  
DE L'USAGER  
POUR PLUS DE  
RENSEIGNEMENTS

XXXXAUB15C1054001  
XXXXAUB15C1054001  
XXXXAUB15C1054001  
XXXXAUB15C1054001

OR BILINGUAL FORMAT

1.875"

MANUFACTURED BY / FABRIQUÉ PAR : ABC MANUFACTURING  
GVWR / PNBV : 1356 KG (2990 LB)  
GAWR / PNBE (EACH AXLE) TIRE / PNEU RIM / JANTE  
1356 KG (2990 LB) ST205/75R15(C) 15 X 6 J 345 KPA (50 PSI) SINGLE  
THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON  
THE DATE OF MANUFACTURE. / CE VÉHICULE EST CONFORME À TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU RÈGLEMENT SUR LA  
SÉCURITÉ DES VÉHICULES AUTOMOBILES DU CANADA EN VIGUEUR À LA DATE DE SA FABRICATION  
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN  
ABOVE  
V.I.N./N.I.V. XXXA1UB15C1054001 TYPE : TRA / REM UTILITY 32' - TA

DATE : 12/2011  
COLD INFL. PRESS. / PRESS.  
DE GONFL. À FROID  
KPA (PSI / LPC)



TIRE AND LOADING INFORMATION  
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should never exceed 810 kg or 1,786 lbs.  
Le poids du chargement ne doit jamais dépasser 810 kg ou 1,786 lb.

| TIRE /<br>PNEU   | SIZE /<br>DIMENSIONS | COLD TIRE PRESS. / PRESS.<br>DES PNEUS À FROID |
|------------------|----------------------|------------------------------------------------|
| RR/AR            | ST205/75R15(C)       | 345 KPA (50 PSI)                               |
| INT/INT          | NONE/AUCUN           |                                                |
| FR/AV            | NONE/AUCUN           |                                                |
| SPARE/DE SECOURS | ST205/75R15(C)       | 345 KPA( 50 PSI)                               |

SEE OWNER'S  
MANUAL FOR  
ADDITIONAL  
INFORMATION  
VOIR LE MANUEL  
DE L'USAGER  
POUR PLUS DE  
RENSEIGNEMENTS

XXXXAUB15C1054001  
XXXXAUB15C1054001  
XXXXAUB15C1054001  
XXXXAUB15C1054001